



Uncoated

Aluminum & Non-Ferrous, Solid Carbide, 3-Flute, Parabolic, 150° Point, 5X Dia., 30° Helix (.5000-.7500)

Drill Size	Decimal Equiv	Flute Length	Drill Depth	OAL	Shank ø	Uncoated Part #
1/2	.5000	3	2-1/4	4-3/4	1/2	RDH3117
13.00MM	.5118	77	60	124	14	RDH3118
33/64	.5156	3-1/4	2-7/16	5	33/64	RDH3119
17/32	.5312	3-1/4	2-7/16	5	17/32	RDH3120
13.50MM	.5315	77	60	124	14	RDH3121
35/64	.5469	3-1/4	2-7/16	5	35/64	RDH3122
14.00MM	.5512	77	60	124	14	RDH3123
9/16	.5625	3-1/4	2-7/16	5	9/16	RDH3124
14.50MM	.5709	83	63	133	16	RDH3125
15.00MM	.5906	83	63	133	16	RDH3126
15.50MM	.6102	83	63	133	16	RDH3127
15.80MM	.6220	83	63	133	16	RDH3128
5/8	.6250	3-1/2	2-5/8	5-1/4	5/8	RDH3129
16.00MM	.6299	83	63	133	16	RDH3130
21/32	.6562	3-5/8	2-23/32	5-1/2	21/32	RDH3131
11/16	.6875	3-5/8	2-23/32	5-1/2	11/16	RDH3132
3/4	.7500	3-7/8	2-29/32	5-3/4	3/4	RDH3133

For detailed tolerance information, see [page 337](#).



[Speeds & Feeds page 337](#).