



| Carbide Threading Bars, Left Hand | | | | | | |
|-----------------------------------|--------|--------------|-------|---------|------------------|---------------------------|
| Minimum Bore | Offset | Max. Depth | OAL | Shank ø | Threads Per Inch | Uncoated Part # |
| .180 | .040 | .500 | 2-1/2 | 1/4 | 18-56 | RTB311200 |
| | .040 | .750 | 2-1/2 | 1/4 | 18-56 | RTB311205 |
| | .040 | 1.000 | 2-1/2 | 1/4 | 18-56 | RTB311210 |
| .200 | .045 | .500 | 2-1/2 | 1/4 | 16-40 | RTB311215 |
| | .045 | .750 | 2-1/2 | 1/4 | 16-40 | RTB311220 |
| | .045 | 1.000 | 2-1/2 | 1/4 | 16-40 | RTB311225 |
| .230 | .055 | .500 | 2-1/2 | 5/16 | 14-40 | RTB311230 |
| | .055 | .750 | 2-1/2 | 5/16 | 14-40 | RTB311235 |
| | .055 | 1.000 | 2-1/2 | 5/16 | 14-40 | RTB311240 |
| .290 | .070 | .500 | 2-1/2 | 5/16 | 12-40 | RTB311245 |
| | .070 | .750 | 2-1/2 | 5/16 | 12-40 | RTB311250 |
| | .070 | 1.000 | 2-1/2 | 5/16 | 12-40 | RTB311255 |
| .320 | .075 | .500 | 2-1/2 | 3/8 | 10-32 | RTB311260 |
| | .075 | .750 | 2-1/2 | 3/8 | 10-32 | RTB311265 |
| | .075 | 1.000 | 2-1/2 | 3/8 | 10-32 | RTB311270 |
| .360 | .085 | .500 | 2-1/2 | 3/8 | 10-32 | RTB311275 |
| | .085 | .750 | 2-1/2 | 3/8 | 10-32 | RTB311280 |
| | .085 | 1.000 | 2-1/2 | 3/8 | 10-32 | RTB311285 |

